

University of Missouri, St. Louis

IRL @ UMSL

---

UMSL Patents

---

10-19-2021

## Method and system for non-invasive blood glucose measurement using signal change of the non-glucose components induced by the presence of glucose

Zhi Xu

zhixu@umsl.edu

Follow this and additional works at: <https://irl.umsl.edu/patents>

---

### Recommended Citation

Xu, Zhi, "Method and system for non-invasive blood glucose measurement using signal change of the non-glucose components induced by the presence of glucose" (2021). *UMSL Patents*. 47.  
<https://irl.umsl.edu/patents/47>

This Book is brought to you for free and open access by IRL @ UMSL. It has been accepted for inclusion in UMSL Patents by an authorized administrator of IRL @ UMSL. For more information, please contact [marvinh@umsl.edu](mailto:marvinh@umsl.edu).



US011147482B2

(12) **United States Patent**  
**Xu**

(10) **Patent No.:** **US 11,147,482 B2**  
(45) **Date of Patent:** **\*Oct. 19, 2021**

(54) **METHOD AND SYSTEM FOR  
NON-INVASIVE BLOOD GLUCOSE  
MEASUREMENT USING SIGNAL CHANGE  
OF THE NON-GLUCOSE COMPONENTS  
INDUCED BY THE PRESENCE OF  
GLUCOSE**

(58) **Field of Classification Search**  
None  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,441,343 A 5/1948 Becker  
3,621,268 A 11/1971 Friedrich et al.  
3,910,701 A 10/1975 Henderson et al.  
3,963,327 A 6/1976 Poirier  
(Continued)

FOREIGN PATENT DOCUMENTS

CN 1192665 9/1998  
CN 2694097 Y 4/2005  
(Continued)

OTHER PUBLICATIONS

Office Action for CN Application 200880114960.3 dated Feb. 17, 2015.

(Continued)

*Primary Examiner* — Patrick Fernandes  
*Assistant Examiner* — Benjamin S Melhus  
(74) *Attorney, Agent, or Firm* — Haverstock & Owens LLP

(57) **ABSTRACT**

A method and system for detecting glucose in a biological sample is disclosed. This includes illuminating a biological sample with a light source, collecting transmitted, reflected or transreflected light from the sample with a detector, generating spectral data of one or more components in the sample other than glucose in a spectral data analysis device, and analyzing the spectral data of the one or more components, sufficient to provide a glucose measurement from the spectral data of the one or more components other than glucose with the spectral data analysis device.

**15 Claims, 8 Drawing Sheets**

(71) Applicant: **St. Louis Medical Devices, Inc.**,  
Sunnyvale, CA (US)

(72) Inventor: **Zhi Xu**, Saint Louis, MO (US)

(73) Assignee: **St. Louis Medical Devices, Inc.**,  
Sunnyvale, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 87 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/773,895**

(22) Filed: **Jan. 27, 2020**

(65) **Prior Publication Data**

US 2020/0155042 A1 May 21, 2020


**Related U.S. Application Data**

(63) Continuation of application No. 12/407,999, filed on Mar. 20, 2009, now Pat. No. 10,542,919.

(60) Provisional application No. 61/039,170, filed on Mar. 25, 2008.

(51) **Int. Cl.**  
*A61B 5/1455* (2006.01)  
*A61B 5/145* (2006.01)

(52) **U.S. Cl.**  
CPC ..... *A61B 5/1455* (2013.01); *A61B 5/14532* (2013.01)



(56)		References Cited					
		U.S. PATENT DOCUMENTS					
3,954,560	A	10/1976	Henderson et al.	7,039,447	B2	5/2006	Berman et al.
4,014,321	A	3/1977	March	7,043,289	B2	5/2006	Fine et al.
4,632,559	A	12/1986	Brunsting	7,107,087	B2	9/2006	Hwang et al.
4,655,225	A	4/1987	Dahne et al.	7,133,711	B2	11/2006	Chemoguz et al.
4,781,195	A	11/1988	Martin	7,215,987	B1	5/2007	Sterling
4,836,782	A	6/1989	Gonser	7,254,432	B2	8/2007	Fine et al.
4,962,311	A	10/1990	Poysel et al.	7,266,400	B2	9/2007	Fine et al.
4,997,769	A	3/1991	Lundsgaard et al.	7,409,239	B2	8/2008	Chung et al.
5,009,230	A	4/1991	Hutchison	7,424,317	B2	9/2008	Parker et al.
5,028,787	A	7/1991	Rosenthal et al.	7,436,511	B2	10/2008	Ruchti et al.
5,077,476	A	12/1991	Rosenthal	7,809,418	B2	10/2010	Xu
5,086,229	A	2/1992	Rosenthal et al.	7,961,305	B2	6/2011	Xu et al.
5,112,124	A	5/1992	Harjunmaa et al.	8,272,771	B2	9/2012	Arai
5,137,023	A	8/1992	Mendelson et al.	8,340,738	B2	12/2012	Xu
5,167,228	A	12/1992	Czeisler	2001/0030742	A1	10/2001	Kramer et al.
5,183,042	A	2/1993	Harjunmaa et al.	2001/0039376	A1	11/2001	Steuer et al.
5,222,496	A	6/1993	Clarke et al.	2001/0047137	A1	11/2001	Moreno et al.
5,255,171	A	10/1993	Clark	2002/0010563	A1	1/2002	Ratteree et al.
5,282,473	A	2/1994	Braig et al.	2002/0016534	A1	2/2002	Trepagnier et al.
5,361,758	A	11/1994	Hall et al.	2002/0019055	A1	2/2002	Brown et al.
5,423,983	A	6/1995	Chiang et al.	2002/0038080	A1	3/2002	Makarewicz et al.
5,448,992	A	9/1995	Kupersmidt	2002/0091324	A1	7/2002	Kollias et al.
5,501,648	A	3/1996	Grigoriev	2002/0161289	A1	10/2002	Hopkins et al.
5,515,847	A	5/1996	Braig et al.	2002/0167704	A1	11/2002	Kleinhans et al.
5,522,388	A	6/1996	Ishikawa et al.	2003/0004423	A1	1/2003	Lavie et al.
5,529,065	A	6/1996	Tsuchiya	2003/0023140	A1	1/2003	Chance
5,535,743	A	7/1996	Backhaus et al.	2003/0023152	A1	1/2003	Abbink et al.
5,553,613	A	9/1996	Parker	2003/0055325	A1	3/2003	Weber et al.
5,576,544	A	11/1996	Rosenthal	2003/0078504	A1	4/2003	Rowe
5,643,334	A	1/1997	Eckhouse et al.	2003/0099574	A1	5/2003	Bentsen
5,615,672	A	4/1997	Braig et al.	2004/0015734	A1	1/2004	Rahman
5,615,673	A	4/1997	Berger et al.	2004/0087844	A1	5/2004	Yen
5,666,956	A	9/1997	Buchert	2004/0106163	A1	6/2004	Workman et al.
5,671,301	A	9/1997	Kupersmidt	2004/0127779	A1	7/2004	Steuer et al.
5,703,364	A	12/1997	Rosenthal	2004/0181132	A1	9/2004	Rosenthal
5,743,262	A	4/1998	Lepper, Jr. et al.	2004/0204865	A1	10/2004	Lee et al.
5,910,109	A	6/1999	Peters et al.	2004/0225205	A1	11/2004	Fine et al.
6,025,597	A	2/2000	Sterling et al.	2004/0225206	A1	11/2004	Kouchnir
6,043,492	A	3/2000	Lee et al.	2005/0131286	A1	6/2005	Parker et al.
6,064,898	A	5/2000	Aldrich	2005/0197790	A1	9/2005	Sterling et al.
6,067,463	A	5/2000	Jeng et al.	2005/0261560	A1	11/2005	Ridder et al.
6,097,975	A	8/2000	Petrovsky et al.	2005/0272987	A1	12/2005	Kian-Azarbayjany et al.
6,134,458	A	10/2000	Rosenthal	2005/0276072	A1	12/2005	Hayashi et al.
6,134,460	A	10/2000	Chance	2006/0002598	A1	1/2006	Rowe et al.
6,151,517	A	11/2000	Honigs et al.	2006/0004268	A1	1/2006	Cho et al.
6,167,290	A	12/2000	Yang et al.	2006/0009685	A1	1/2006	Finarov et al.
6,181,958	B1	1/2001	Steuer et al.	2006/0058622	A1	3/2006	Tearney et al.
6,205,354	B1	3/2001	Gellermann et al.	2006/0063983	A1	3/2006	Yamakoshi
6,208,788	B1	3/2001	Nosov	2006/0092643	A1	5/2006	Wong et al.
6,304,767	B1	10/2001	Soller et al.	2006/0129040	A1	6/2006	Fine et al.
6,312,393	B1	11/2001	Abreu	2006/0152726	A1	7/2006	Larsen et al.
6,337,564	B2	1/2002	Manzini et al.	2006/0200014	A1	9/2006	Fine et al.
6,403,944	B1	6/2002	MacKenzie et al.	2006/0224057	A1	10/2006	Burd et al.
6,412,548	B1	7/2002	Berman et al.	2006/0226992	A1	10/2006	Al-Ali et al.
6,424,848	B1	7/2002	Berman et al.	2006/0234386	A1	10/2006	Burns et al.
6,424,849	B1	7/2002	Berman et al.	2006/0250676	A1	11/2006	Hagood
6,424,851	B1	7/2002	Berman et al.	2006/0258918	A1	11/2006	Burd et al.
6,430,424	B1	9/2002	Berman et al.	2006/0264719	A1	11/2006	Schurman et al.
6,445,938	B1	9/2002	Berman et al.	2007/0049811	A1	3/2007	Kobayashi et al.
6,522,903	B1	2/2003	Berman et al.	2007/0078312	A1	4/2007	Fine et al.
6,574,490	B2	6/2003	Abbink et al.	2007/0112258	A1	5/2007	Soyemi et al.
6,671,528	B2	12/2003	Steuer et al.	2007/0149869	A1	6/2007	Yen
6,684,099	B2	1/2004	Ridder et al.	2008/0027297	A1	1/2008	Yamakoshi
6,723,048	B2	4/2004	Fuller	2008/0137066	A1	6/2008	Weinstein
6,731,963	B2	5/2004	Finarov et al.	2008/0144004	A1	6/2008	Rosenthal
6,775,564	B1	8/2004	Peters et al.	2008/0194014	A1	8/2008	Young et al.
6,804,002	B2	10/2004	Fine et al.	2008/0266900	A1	10/2008	Harbers et al.
6,833,540	B2	12/2004	MacKenzie et al.	2008/0316488	A1	12/2008	Mao
6,865,408	B1	3/2005	Abbink et al.	2009/0059586	A1	3/2009	Livesay et al.
6,873,865	B2	3/2005	Steuer et al.	2009/0079964	A1	3/2009	Xu
6,958,039	B2	11/2005	Burd et al.	2009/0105565	A1	4/2009	Xu
6,968,222	B2	11/2005	Burd et al.	2009/0105605	A1	4/2009	Abreu
6,990,365	B1	1/2006	Parker et al.	2009/0116017	A1	5/2009	Xu et al.
6,993,372	B2	1/2006	Fine et al.	2009/0196025	A1	8/2009	Joseph et al.
7,039,446	B2	5/2006	Ruchti et al.	2009/0247843	A1	10/2009	Xu
				2009/0270700	A1	10/2009	Van Herpen et al.
				2009/0292186	A1	11/2009	Xu
				2010/0026995	A1	2/2010	Merrit et al.
				2010/0252721	A1	10/2010	Xu

(56) **References Cited**  
U.S. PATENT DOCUMENTS

2013/0006070 A1 1/2013 Xu  
2013/0006072 A1 1/2013 Xu  
2013/0006073 A1 1/2013 Xu

FOREIGN PATENT DOCUMENTS

CN 1932840 A 3/2007  
EP 0160768 A1 11/1985  
EP 0319159 A1 6/1989  
EP 0781527 A1 7/1997  
EP 01094745 A1 5/2001  
EP 1281370 A2 2/2003  
EP 1300712 A2 4/2003  
EP 830582 B1 8/2005  
GB 810256 A 3/1959  
JP 56-156138 A 12/1981  
JP 02-191434 A 7/1990  
JP 07-088105 A 4/1995  
JP 720551 U 4/1995  
JP 9010238 1/1997  
JP H0956702 A 3/1997  
JP 11037931 A 2/1999  
JP 11-178813 A 7/1999  
JP 2000083933 A 3/2000  
JP 2003245265 A 9/2003  
JP 2004267613 A 9/2004  
JP 2004286475 A 10/2004  
JP 2004290544 A 10/2004  
JP 2004538054 A 12/2004  
JP 2005283563 A 10/2005  
JP 2007185348 A 7/2007  
JP 2009545344 A 12/2009  
RU 2050545 C1 12/1995  
RU 2188425 C2 8/2002  
RU 2198402 C2 2/2003  
SU 1193541 A1 11/1985  
WO 90/130922 A1 11/1990  
WO 1991015991 A1 10/1991  
WO 1991015992 A1 10/1991  
WO 92/00513 A1 1/1992  
WO 1993000856 A1 1/1993  
WO 93/06774 A1 4/1993  
WO 93/16629 A1 9/1993  
WO 1994013199 A1 6/1994  
WO 1994016614 A1 8/1994  
WO 95/05599 A1 2/1995  
WO 1995031930 A1 11/1995  
WO 1996004840 A1 2/1996  
WO 1996017546 A1 6/1996  
WO 96/39926 A1 12/1996  
WO 96/41151 A1 12/1996  
WO 1996039927 A1 12/1996  
WO 1998003847 A2 1/1998  
WO 1998036681 A1 8/1998  
WO 99/16136 A1 4/1999  
WO 199939631 A1 8/1999  
WO 2000001294 A1 1/2000  
WO 2000016688 A1 3/2000  
WO 01/16578 A1 3/2001  
WO 2001093755 A1 12/2001  
WO 2001096872 A2 12/2001  
WO 2002082990 A1 10/2002  
WO 03001177 A2 1/2003  
WO 2003010510 A2 2/2003  
WO 03/077756 A1 9/2003  
WO 2003079900 A1 10/2003  
WO 2005045377 A2 5/2005  
WO 2006086566 A2 8/2006  
WO 2006094109 A1 9/2006  
WO 2007122557 A2 11/2007  
WO 2008014890 A1 2/2008  
WO 2008/039195 A1 4/2008  
WO 2009/035669 A1 3/2009  
WO 2009/045492 A1 4/2009  
WO 2009/120600 A2 10/2009

WO 2009/142853 A1 11/2009  
WO 2010017238 A1 2/2010  
WO 2010114736 10/2010

OTHER PUBLICATIONS

Office Action for EP Application 09751083.8 dated Feb. 24, 2015.  
Office Action for CN Application 201310489245.0 dated Feb. 26, 2015.  
Office Action for CA Application 2699626 dated Feb. 27, 2015.  
Office Action for JP Application 2012-503498 dated Mar. 31, 2015.  
Office Action dated for RU Application 2011144084 dated Apr. 17, 2015.  
Office Action for CA Application 2700996 dated Aug. 7, 2015.  
Office Action for U.S. Appl. No. 12/407,999 dated Jan. 5, 2016.  
Office Action for JP Application 2014-245584 dated Jan. 5, 2016, includes English Translation.  
Office Action for CN Application 201310489245 dated Jan. 25, 2016.  
Office Action for EP Application 9751083.8 dated Jan. 26, 2016.  
Extended European Search Report for EP Application 08836010.2 dated Mar. 8, 2016.  
Office Action for U.S. Appl. No. 13/610,423 dated Mar. 24, 2016.  
Office Action for CA Application 2789658 dated Mar. 30, 2016.  
Office Action for U.S. Appl. No. 13/610,342 dated Apr. 14, 2016.  
Office Action for U.S. Appl. No. 13/610,387 dated Apr. 14, 2016.  
Office Action for U.S. Appl. No. 13/610,140 dated May 13, 2016.  
International Preliminary Report on Patentability (Chapter II) for PCT/US2009/037805 dated Dec. 14, 2010.  
First Examination Report dated Oct. 27, 2017 for the Indian Application No. 1186/KOLNP/2010.  
European Search Report from European Application No. 17159427.8.  
Attached please find the Office Action dated Jun. 30, 2017 for the Indian application No. 4886/KOLNP/2010.  
Texas Instruments TSL260, TSL261, TSL262 IR Light-to-Voltage Optical Sensors 1993.  
Indian Examination Report dated Apr. 13, 2018, Application No. 41144/KOLNP/2011.  
European First Examination Report dated Jun. 4, 2018. EP Application No. 10759220.6.  
Unfavorable opinion dated Jul. 31, 2019 for Brazilian Application No. PI01816925-0.  
European Search Report dated Aug. 21, 2019 for European Application No. 19178081.6.  
The Office Action dated Dec. 21, 2018 for Brazilian Patent Application No. PI0816925-0.  
The Office Action dated May 21, 2019 for Brazilian Patent Application No. PI0909825-9.  
Wagner et al., "Invasiveness as a Barrier to Self-Monitoring of Blood Glucose in Diabetes", Diabetes Technology & Therapeutics, Aug. 1, 2005.  
Web Page Document entitled [http://www.orense.com/Diabetes\\_Monitoring](http://www.orense.com/Diabetes_Monitoring) dated Aug. 9, 2007.  
International Search Report for PCT/US/2008/010670 dated Nov. 21, 2008.  
International Search Report for PCT/US/2008/011438 dated Dec. 9, 2008.  
Office Action for U.S. Appl. No. 12/209,807 dated May 17, 2010.  
International Search Report and Written Opinion for PCT/US2010/028255 dated May 19, 2010.  
Office Action for U.S. Appl. No. 12/256,028 dated May 24, 2010.  
International Preliminary Report on Patentability (Chapter II) for PCT/US2008/011438 dated Jun. 18, 2010.  
Office Action for U.S. Appl. No. 12/256,028 dated Sep. 15, 2010.  
Office Action for U.S. Appl. No. 12/209,807 dated Sep. 17, 2010.  
International Preliminary Report on Patentability (Chapter II) for PCT/US2009/040942 dated Dec. 13, 2010.  
Office Action for U.S. Appl. No. 12/425,535 dated Mar. 22, 2012.  
Office Action for U.S. Appl. No. 12/407,999 dated Apr. 6, 2012.  
Office Action for U.S. Appl. No. 12/425,535 dated May 16, 2012.

(56)

**References Cited**

OTHER PUBLICATIONS

Office Action for CN Application 200980126116.7 dated Jun. 4, 2012.  
Office Action for RU Application 2010117396 dated Jun. 18, 2012.  
Office Action for RU Application 2010114587 dated Jun. 22, 2012.  
Office Action for U.S. Appl. No. 12/729,886 dated Oct. 2, 2012.  
Office Action for U.S. Appl. No. 12/407,999 dated Nov. 21, 2012.  
Office Action for JP Application 2010-524873 dated Dec. 25, 2012.  
Office Action for JP Application 2010-527994 dated Dec. 25, 2012.  
Office Action for CN Application 200880114960.3 dated Jan. 29, 2013.  
Office Action for CN Application 200980126116.7 dated Feb. 16, 2013.  
Office Action for U.S. Appl. No. 12/729,886 dated Mar. 12, 2013.  
Office Action for RU Application 2010152373 dated Mar. 26, 2013.  
Extended European Search Report for EP Application 08830786.3 dated Apr. 22, 2013.  
Office Action for JP Application 2011-501936 dated Jun. 25, 2013.  
Office Action for CN Application 201080022242.0 dated Jul. 4, 2013.  
Extended European Search Report for EP Application 09751083.8 dated Jul. 26, 2013.  
Office Action for AU Application 2010232841 dated Aug. 13, 2013.  
Office Action for AU Application 2008299938 dated Sep. 13, 2013.  
Office Action for U.S. Appl. No. 12/407,999 dated Oct. 10, 2013.  
Office Action for CN Application 200980126116.7 dated Oct. 17, 2013.  
Office Action for JP Application 2010-524873 dated Nov. 19, 2013.

Office Action for JP Application 2011-510533 dated Dec. 3, 2013.  
Examiner's Decision of Rejection for JP Application 2010-527994 dated Dec. 10, 2013.  
Office Action for CN Application 201210419849.3 dated Jan. 6, 2014.  
Office Action for EP Application 08830786.3 dated Jan. 10, 2014.  
Office Action for CN Application 201210420843.8 dated Feb. 17, 2014.  
Office Action for CN Application 201210419740.X dated Feb. 28, 2014.  
Office Action for CN Application 201080022242.0 dated Mar. 12, 2014.  
Office Action for RU Application 2010114587 dated Mar. 25, 2014.  
Office Action for EP Application 09751083.8 dated Mar. 28, 2014.  
Office Action for CA Application 2700996 dated Jul. 30, 2014.  
Office Action for JP Application 2011-501936 dated Aug. 5, 2014.  
Office Action for U.S. Appl. No. 12/407,999 dated Nov. 20, 2014.  
Office Action for CN Application 201210420830.0 dated Jan. 5, 2015.  
Office Action for U.S. Appl. No. 13/610,342 dated Jan. 21, 2015.  
Office Action for U.S. Appl. No. 13/610,423 dated Jan. 22, 2015.  
Office Action for U.S. Appl. No. 13/610,387 dated Jan. 22, 2015.  
The Office Action dated Jul. 7, 2020 for the Brazilian application No. PI1010304-0.  
The Official Letter dated Mar. 19, 2021 for the European Patent Application No. 08836010.2.  
The Decision for Refusal dated Feb. 13, 2020, from European Patent application No. EP10 759 220.6.  
The Hearing Notice dated Nov. 8, 2019 from Indian Patent application No. 1186/KOLNP/2010.




FIG.1




FIG. 2A




FIG. 2B






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

1

**METHOD AND SYSTEM FOR  
NON-INVASIVE BLOOD GLUCOSE  
MEASUREMENT USING SIGNAL CHANGE  
OF THE NON-GLUCOSE COMPONENTS  
INDUCED BY THE PRESENCE OF  
GLUCOSE**

CROSS-REFERENCE TO RELATED  
APPLICATION

This patent application is a continuation of the co-pending U.S. patent application Ser. No. 12/407,999, published as U.S. Patent Application Publication No. 2009/0247843, filed on Mar. 20, 2009, titled "Method and System for Non-Invasive Blood Glucose Detection Utilizing Spectral Data of One or More Components Other Than Glucose," which claims priority to U.S. Provisional Patent Application Ser. No. 61/039,170 filed Mar. 25, 2008, the disclosure of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

Diabetes is a chronic disease that, when not controlled, over time leads to serious damage to many of the body's systems, including the nerves, blood vessels, eyes, kidneys and heart. The National Institute of Diabetes and Digestive and Kidney Diseases (NIDDK) estimates that 23.6 million people or 7.8 percent of the population in the United States have diabetes in 2007. Globally, the World Health Organization (WHO) estimates that more than 180 million people have diabetes, a number they expect to increase to 366 million by 2030, with 30.3 million in the United States. According to the WHO, an estimated 1.1 million people died from diabetes in 2005. They project that diabetes deaths will increase by more than 50% between 2006 and 2015 overall and by more than 80% in upper-middle income countries.

The economic burden from diabetes for individuals and society as a whole is substantial. According to the American Diabetes Association, the total annual economic cost of diabetes was estimated to be \$174 billion in the United States in 2007. This is an increase of \$42 billion since 2002. This 32% increase means the dollar amount has risen over \$8 billion more each year.

A vital element of diabetes management is the self-monitoring of blood glucose (SMBG) concentration by diabetics in the home environment. By testing blood glucose levels often, diabetics can better manage medication, diet and exercise to maintain control and prevent the long-term negative health outcomes. In fact, the Diabetes Control and Complications Trial (DCCT), which followed 1,441 diabetics for several years, showed that those following an intensive-control program with multiple blood sugar tests each day as compared with the standard-treatment group had only one-fourth as many people develop diabetic eye disease, one-half as many develop kidney disease, one-third as many develop nerve disease, and far fewer people who already had early forms of these three complications got worse.

However, current monitoring techniques discourage regular use due to the inconvenient and painful nature of drawing blood through the skin prior to analysis, which causes many diabetics to not be as diligent as they should be for good blood glucose control. As a result, non-invasive measurement of glucose concentration is a desirable and beneficial development for the management of diabetes. A non-invasive monitor will make testing multiple times each day pain-free and more palatable for children with diabetes. According to a study published in 2005 (J. Wagner, C.

2

Malchoff, and G. Abbott, *Diabetes Technology & Therapeutics*, 7(4) 2005, 612-619), people with diabetes would perform SMBG more frequently and have improved quality of life with a non-invasive blood glucose monitoring device.

5 Currently, there remains a concentrated effort in academia and industry to develop reliable, affordable non-invasive blood glucose monitors. One technique of non-invasive blood chemicals detection involves collecting and analyzing light spectra data. Extracting information about blood characteristics such as glucose concentration from spectral or other data obtained from spectroscopy is a complex problem due to the presence of components (e.g., skin, fat, muscle, bone, interstitial fluid) other than blood in the area that is being sensed. Such other components can influence these signals in such a way as to alter the reading. In particular, the resulting signal may be much larger in magnitude than the portion of the signal that corresponds to blood and therefore limits the ability to accurately extract blood characteristics information.

The prevailing view is to correlate the change in optical absorption at certain wavelengths with blood glucose concentration, while ignoring the fact that similar changes in optical absorption could also be caused by other factors, such as physical exercise, medication, emotion, or a change in body chemistry, such as endocrine levels, etc. As such, good correlations obtained in well controlled laboratory conditions do not translate into successful, reliable market devices.

The present invention is directed to overcoming one or more of the problems set forth above.

SUMMARY OF INVENTION

Embodiments of the present invention relate to a method for detecting glucose in a biological sample. The method includes illuminating a biological sample with a light source, collecting transmitted, transflected or reflected light from the sample, generating spectral data of one or more components in the sample other than glucose and analyzing the spectral data of the one or more components sufficient to provide a glucose concentration measurement from the spectral data of the one or more components other than glucose.

These are merely some of the innumerable aspects of the present invention and should not be deemed an all-inclusive listing of the innumerable aspects associated with the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the present invention, reference may be made to accompanying drawings, in which:

FIG. 1 illustrates a block flow diagram of a method for detecting glucose in a biological sample, according to some embodiments;

FIGS. 2A and 2B illustrate plots of a pulse wave corresponding to light absorption of arterial blood in a human finger, according to some embodiments;

FIG. 3 illustrates a graphical view of a water absorbance spectrum, according to some embodiments;

FIG. 4 illustrates a graphical view of an absorbance spectrum of a 1250 mg/dL glucose solution, according to some embodiments;

FIG. 5 illustrates a graphical view of an absorbance spectrum of a 2500 mg/dL glucose solution, according to some embodiments;

FIG. 6 illustrates a graphical view of differential water spectrum, according to some embodiments; and

FIG. 7 illustrates a system for detecting glucose in a biological sample, according to some embodiments.

#### DETAILED DESCRIPTION OF THE INVENTION

In the following detailed description, numerous exemplary specific details are set forth in order to provide a thorough understanding of the invention. However, it will be understood by those skilled in the art that the present invention may be practiced without these specific details, or with various modifications of the details. In other instances, well known methods, procedures, and components have not been described in detail so as not to obscure the present invention.

Embodiments of the invention relate to a method for non-invasive blood glucose detection. Glucose has extremely weak optical absorption in the visible (Vis) and near infrared (NIR) regions from about 400 nm to about 2500 nm. It is very difficult to accurately determine the concentration of glucose in a biological sample by determining the portion of optical absorption generated by glucose in the biological sample, because the portion of optical absorption by other components is typically several orders of magnitude larger than that directly by glucose in the two wavelength regions. But, glucose can induce changes in the optical absorption of other components in the sample, such as hemoglobin or water. These changes in optical absorption of components other than glucose can be used to indirectly determine the concentration of glucose in a biological sample.

Referring to FIG. 1, a block flow diagram of a method for detecting glucose in a biological sample is shown, according to some embodiments and is generally indicated by numeral 100. In the description of the flowcharts, the functional explanation marked with numerals in angle brackets <nnn>, will refer to the flowchart blocks bearing that numeral. A biological sample may be illuminated with a light source <102>. Transmitted, transflected or reflected light may then be collected from the sample <104>. Spectral data of one or more components in the sample other than glucose may be generated <106>. The spectral data of the one or more components may be analyzed, sufficient to provide a glucose concentration measurement from the spectral data of the one or more components other than glucose <108>.

Illuminating <102> may refer to exposing the biological sample to a light source in the visible (Vis), near infrared (NIR) or mid-infrared spectral regions. The wavelength range for illumination <102> may occur between about 400 nm and about 10,000 nm, for example. The illuminating <102> may occur between about 400 nm and about 2500 nm or about 400 nm and about 1000 nm, for example. The light source may be lasers, light emitting diodes (LED), incandescent lamps, halogen lamps or a combination thereof, for example. The light source may be a plurality of lasers. Prior to or after illumination of the sample <102>, a reference sample may be illuminated for calibration.

The biological sample may be any portion of the human body that contains glucose or has the potential to contain glucose. The biological sample may be a human finger, toe, ear lobe, tongue or arm, for example.

After illumination <102>, transmitted, transflected or reflected light may then be collected from the sample <104>.

The light may be collected by one or more detectors or light-sensing devices. An array of photodiodes may be utilized, for example.

Spectral data of one or more components in the sample other than glucose may be generated <106>. The detector may generate a corresponding current signal that is proportional to the power of the light received by the detector. The current signal generated by the detector can be converted to another form of signal, such as an analog voltage signal or a digital signal. Such signals may be converted to spectral or absorbance data using known processors and algorithms.

The spectral data of the one or more components may be analyzed <108>, sufficient to provide a glucose concentration measurement from the spectral data of the one or more components other than glucose.

Spectroscopic data generation <106> and analysis <108> may be carried out using a pulsatile or a stationary methodology.

A pulsatile data generation and analysis methodology has been described in presently owned U.S. patent application Ser. No. 12/245,298, filed Oct. 3, 2008, which is incorporated herein by reference and U.S. patent application Ser. No. 12/209,807, filed Sep. 12, 2008, which is incorporated herein by reference. When light is transmitted through a biological sample, such as a human finger, the light is absorbed and scattered by various components of the finger including muscle, bone, fat and blood. It has been observed, however, that light absorption by a human finger exhibits a small cyclic pattern that corresponds to a heartbeat.

FIG. 2A depicts a plot 202 of a pulse wave that corresponds to the light absorption of arterial blood in the capillary due to the heartbeat of the user. Although the magnitude of the cyclic pattern is small in comparison to the total photocurrent generated by the detector, considerable information can be extracted from the cyclic pattern of the plot 202. For example, assuming that the person's heart rate is sixty beats per minute, the time between the start of any pulse beat and the end of that pulse beat is one second. During this one-second period, the plot will have a maximum or peak 204 reading and minimum or valley 206 reading. The peak 204 reading of the plot corresponds to when there is a minimum amount of blood in the capillaries, and the valley 206 reading corresponds to when there is a maximum amount of blood in the capillaries. By using optical information provided by the peak and valley of the cyclic plot, the major constituents that are in the body that are not in the capillaries, such as fat, muscle (i.e., protein) and interstitial fluid, are excluded. These major constituents that are not in the capillaries are excluded because they are not likely to change during the one-second interval. In other words, the light that is impeded by the blood can be detected based on the peaks and valleys of the plot 202. FIG. 2A illustrates the cyclic pattern on a magnified scale. FIG. 2B depicts a more accurate reflection of the cyclic pattern in terms of signal amplitude.

In a stationary data acquisition and analysis methodology, the light absorption is averaged over a period of time to remove the fluctuation in light absorption due to the heartbeat. The glucose concentration can be extracted from the averaged light absorption at different wavelengths over the same period of data acquisition time.

Referring again to FIG. 1, analyzing <108> may also include mathematically comparing the changes in absorbance of the one or more components to changes in glucose concentration. Analyzing <108> may include eliminating spectral data of the one or more components for changes in absorbance not related to interactions with glucose.

5

Because glucose in the biological sample has such a weak optical signal in the Vis and NIR spectral range, the methods of the present invention do not attempt to analyze the glucose signal. Glucose does physically or chemically interact with one or more components in the blood and induce changes in the optical signal of these components as a function of glucose concentration. By analyzing the changes in the one or more components, the concentration of glucose in the sample may be determined.

## EXAMPLE

FIG. 3 shows the NIR spectrum of water between 850 nm to 1100 nm. A strong positive peak is seen between about 920 nm and 1070 nm. The spectrum was taken with a Perkin-Elmer™ Lambda-14™ Double Beam UV-Vis-NIR (190 nm to 1100 nm) spectrometer. The scanning speed was 30 nm/min, the spectrum resolution was 4 nm, and one data point was collected per nm. The reference was the air and the sample was HPLC grade water in a quartz cuvette with 1 cm light path. The baseline absorbance of the spectrum, about 0.05, is due to reflections from two air/quartz interfaces and two water/quartz interfaces.

FIG. 4 shows the absorbance spectrum of a 1250 mg/dL solution of alfa-D(+)-glucose in HPLC grade water, and FIG. 5 shows the absorbance spectrum a 2500 mg/dL solution of alfa-D(+)-glucose in HPLC grade water. The two spectra were taken under the same condition as the water spectrum in FIG. 3, except that the quartz cuvette containing HPLC grade water was used as the reference. To minimize the effect of temperature on water absorption, the two glucose solutions and HPLC grade water were equilibrated in the sample chamber of the spectrometer for four hours before the measurements.

Both FIG. 4 and FIG. 5 show a large negative peak at about 960 nm, about  $-0.0018$  for the 1250 mg/dL glucose solution and about  $-0.0030$  for the 2500 mg/dL glucose solution. This negative peak is not caused by the optical absorption of glucose in this region. Instead, it is a result of change in water absorption due to the presence of glucose. This is supported by the simulated differential water spectrum in FIG. 6. The simulated differential water spectrum was obtained by manually red shifting 1 nm of all data points in the water spectrum of FIG. 3, then subtracting the original water spectrum from the red shifted spectrum. FIG. 6 shows a negative peak centered at 960 nm with a very similar peak shape as those of FIG. 4 and FIG. 5.

FIG. 7 shows an exemplary system for conducting an embodiment of the present invention that is generally indicated by numeral 700. The system of FIG. 7 comprises a light source 701, biological sample 703, detector 705, and spectral data analysis device 707. A light source 701 may be lasers, light emitting diodes (LED), incandescent lamps, halogen lamps or a combination thereof, for example. The light source may be a plurality of lasers. A biological sample 703 may be a human finger, toe, ear lobe, tongue or arm. A detector 705 may be any of a wide variety of light detectors with an illustrative, but nonlimiting, example being an array of photodiodes. Spectral data analysis device 707 may be any device capable of analyzing spectral data as described herein. An illustrative, but nonlimiting, example of a spectral data analysis device 707 may include an SR760™ from Stanford Research Systems, which is a single-channel 100 kHz FFT spectrum analyzers with a dynamic range of 90 dB and a real-time bandwidth of 100 kHz.

Thus, there has been shown and described several embodiments of a novel invention. As is evident from the

6

foregoing description, certain aspects of the present invention are not limited by the particular details of the examples illustrated herein, and it is therefore contemplated that other modifications and applications, or equivalents thereof will occur to those skilled in the art. The terms “have,” “having,” “includes” and “including” and similar terms as used in the foregoing specification are used in the sense of “optional” or “may include” and not as “required.” Many changes, modifications, variations and other uses and applications of the present construction will, however, become apparent to those skilled in the art after considering the specification and the accompanying drawings. All such changes, modifications, variations and other uses and applications which do not depart from the spirit and scope of the invention are deemed to be covered by the invention which is limited only by the claims that follow.

The invention claimed is:

1. A method for measuring a blood glucose concentration comprising:

- a) illuminating a biological sample with a light beam from a light generating device; and
- b) receiving and analyzing an induced change of a light signal of one or more non-blood glucose components from the sample with a detector,

wherein the induced change of the light signal is caused by physical or chemical interaction of glucose with the one or more non-blood glucose components;

wherein the analyzing of the induced change of the light signal comprises:

- generating spectral data, having peaks and valleys, of the one or more non-blood glucose components;
- analyzing spectral data of the one or more blood components, wherein the one or more blood components are non-blood glucose, to provide a blood glucose measurement by measuring light absorption based on peaks and the valleys of the spectral data, which excludes an interference of a measurement by fat, muscle, and interstitial fluid, without analyzing a glucose signal,

wherein the light absorption measured of the one or more non-blood glucose components contains a change of an absorption amount that is induced by an amount of a presence of the blood glucose which is used to indirectly determine the concentration of the blood glucose.

2. The method of claim 1, wherein the light generating device comprises a Laser, a light emitting diode (LED), an incandescent lamp, a halogen lamp or a combination thereof.

3. The method of claim 1, further comprising eliminating light signal data of the one or more non-blood glucose components for changes in absorbance not related to interactions with the glucose.

4. The method of claim 1, further comprising forming a Visible or NIR spectra using the light signal.

5. A blood glucose concentration measuring device comprising:

- a) a light generating device configured to illuminate a biological sample with a light beam; and
- b) a programmable computing device comprising light photocurrent sensors configured to receive and analyze an induced change of a light signal of one or more non-blood glucose components from the sample with a detector,

wherein the induced change of the light signal is caused by the physical or chemical interaction of glucose with the one or more non-blood glucose components;



wherein the programmable computing device analyzes the induced change of the light signal by:

generating spectral data, having peaks and valleys, of the one or more non-blood glucose components; analyzing spectral data of the one or more blood components, wherein the one or more blood components are non-blood glucose, to provide a blood glucose measurement by measuring light absorption based on peaks and the valleys of the spectral data, which excludes an interference of a measurement by fat, muscle, and interstitial fluid, without analyzing a glucose signal,

wherein the light absorption measured of the one or more non-blood glucose components contains a change of an absorption amount that is induced by an amount of a presence of the blood glucose which is used to indirectly determine the concentration of the blood glucose.

6. The device of claim 5, wherein the light generating device comprises a Laser, a light emitting diode (LED), an incandescent lamp, a halogen lamp or a combination thereof.

7. The device of claim 5, wherein the programmable computing device is configured to eliminate the light signal data of the one or more non-blood glucose components for changes in absorbance not related to interactions with the glucose.

8. The device of claim 5, wherein the programmable computing device is configured to form a Visible or NIR spectra using the light signal.

9. A system for detecting blood glucose in a biological sample, comprising:

- a) a light generating device configured to illuminate a biological sample comprising a plurality of blood components;
- b) a detector configured to collect transmitted, transflected or reflected light from the biological sample; and

c) a computing device configured to generate spectral data, having peaks and valleys, of the one or more non-blood glucose components; analyze spectral data of the one or more blood components, wherein the one or more blood components are non-blood glucose, to provide a blood glucose measurement by measuring light absorption based on peaks and the valleys of the spectral data, which excludes an interference of a measurement by fat, muscle, and interstitial fluid, without analyzing a glucose signal, wherein the light absorption measured of the one or more non-blood glucose components contains a change of an absorption amount that is induced by an amount of a presence of the blood glucose which is used to indirectly determine the concentration of the blood glucose.

10. The system of claim 9, wherein the light generating device comprises lasers, light emitting diodes, halogen lamps, incandescent lamps or a combination thereof.

11. The system of claim 9, wherein the light generating device is configured to emit light in at least one of near infrared, mid-infrared and visible light regions.

12. The system of claim 9, wherein the light generating device is configured to emit light having a wavelength in a range of 400 nm to 2500 nm.

13. The system of claim 9, wherein the computing device is configured to mathematically compare changes in absorbance of the one or more blood components to changes in blood glucose concentration.

14. The system of claim 9, wherein the computing device is configured to eliminate portions of the spectral data that are attributable to changes in absorbance not related to interactions with blood glucose.

15. The system of claim 9, wherein the biological sample comprises a portion of at least one of a human finger, toe, ear lobe, tongue or arm.

\* \* \* \* \*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 11,147,482 B2  
APPLICATION NO. : 16/773895  
DATED : October 19, 2021  
INVENTOR(S) : Zhi Xu

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Specification


In the Detailed Description Of The Invention, Column 5, Line 13:

Replace “am” with – nm –

In the Detailed Description Of The Invention, Column 5, Line 56:

Replace “car” with – ear –

Signed and Sealed this  
Thirteenth Day of September, 2022



Katherine Kelly Vidal  
*Director of the United States Patent and Trademark Office*